

FABENCo, Inc.

"The Safety Gate Company"

Mounting Tips for The FabEnCo Self-Closing Safety Gate

U.S. Pat. # 3,866,356

The FabEnCo Self-Closing Safety Gate can be easily installed in minutes on all types of handrails (angle, flatbar, pipe) or to existing walls. It can be mounted left or right, on either side of a handrail, at different levels. The Safety Gate's stainless steel spring returns after each passage and adjustment bolts provide positive stop without handrail contact.

PARTS

Hardware Packet

	<u>QUANTITY</u>
A. U-Bolt*	1
B. J-Bolt*	1
C. 1/2" Hex Bolts	2
D. 1/2" Nuts	4
E. 3/8" Nuts	2
F. 3/8" Washers	2
G. Channels	2
H. Mounting Plate/Frame Assembly (with 2 adjustable stop bolts)	1

*Use U-Bolt for installation on pipes and J-Bolt for installation on angles.

STEP 1

Insert the **U-Bolt** (or **J-Bolt**) through the slot in the **Mounting Plate/Frame Assembly** and fasten to the handrail with the **3/8" Washer(s)** and **3/8" Nut(s)**.

STEP 2

Insert the **1/2" Bolts** through the set of holes (at the desired level) on one **Channel**, then through the **Mounting Plate/Frame Assembly**. Fasten the **1/2" Nuts** onto the **1/2" Bolts** and tighten flush against the **Mounting Plate/Frame Assembly** to stabilize.

STEP 3

Place the second **Channel** on the other side of the handrail and tighten with the remaining **1/2" Nuts**.

SUGGESTED TOOLS

Adjustable Wrench
Socket Set with 7/8" and 11/16" Sockets

For additional information or assistance, call 1-800-962-6111.

